



AR-009-166

Department of Defence

DISTRIBUTION STATEMENT A

Approved for public release
Distribution Unlimited

VISITS BY NUCLEAR POWERED WARSHIPS TO AUSTRALIAN PORTS

Report on Radiation Monitoring During 1994

APPROVED FOR PUBLIC RELEASE

© Commonwealth of Australia

DTIC QUALITY INSPECTED 2

**Canberra, Australia
1995**

19961009 144

**VISITS BY
NUCLEAR POWERED WARSHIPS
TO AUSTRALIAN PORTS**

Report on Radiation Monitoring During 1994

**Department of Defence
Canberra, Australia
1995**

CONTENTS

	Page
CONTENTS SUMMARY	3-4 5
	Paragraph
PART I	GENERAL
INTRODUCTION	1-2
THE RADIATION MONITORING PROGRAM	3-11
Environmental Monitoring	5-10
Direct Radiation Monitoring	11
PROGRAM IMPLEMENTATION	12-15
The Monitoring Program	12-14
Contingency Arrangements	15
PART II	NUCLEAR POWERED WARSHIP VISITS IN 1994
DARWIN NORTHERN TERRITORY	16-19
VISIT BY USS HELENA	16
Radiation Monitoring	17
Results	18-19
FREMANTLE (GAGE ROADS)	20-3
VISIT BY USS CARL VINSON	20
Radiation Monitoring	21
Results	22-3
HMAS STIRLING, GARDEN ISLAND, WESTERN AUSTRALIA	24-35
VISIT BY USS ARKANSAS	24
Radiation Monitoring	25
Results	26-7
VISIT BY USS ASHEVILLE	28
Radiation Monitoring	29
Results	30-1
VISITS BY USS INDIANAPOLIS	32
Radiation Monitoring	33
Results	34-5
MELBOURNE VICTORIA	36-9
VISIT BY USS ARKANSAS	36
Radiation Monitoring	37
Results	38-9
HOBART TASMANIA	40-7
VISIT BY CARL VINSON	40
Radiation Monitoring	41
Results	42-3
VISIT BY USS INDIANAPOLIS	44
Radiation Monitoring	45
Results	46-7

BRISBANE QUEENSLAND	48-51
VISIT BY USS OMAHA	48
Radiation Monitoring	49
Results	50-1

PART III MARINE ENVIRONMENTAL SAMPLING

Measurement Method	52
Detection Capability	53-4
Marine Environmental Monitoring	55-6

PART IV CONCLUSIONS

SUMMARY

Eleven visits were made by six Nuclear Powered Warships (NPW) of the United States Navy to Australian ports in 1994 as follows:

Port	Ship	Dates
Darwin	USS HELENA	1-7 March
Fremantle (Gage Roads)	USS CARL VINSON	5-10 July
HMAS STIRLING Western Australia	USS ARKANSAS	5-10 July
	USS ASHEVILLE	5-10 July
	USS INDIANAPOLIS	20-24 October
	USS INDIANAPOLIS	4-6 November
	USS INDIANAPOLIS	13-16 November
Melbourne	USS ARKANSAS	16-22 July
Hobart	USS CARL VINSON	17-22 July
	USS INDIANAPOLIS	20-23 November
Brisbane	USS OMAHA	19-24 August

The Commonwealth Government requires that a radiation monitoring program be carried out in association with each visit to detect any release of radioactivity to the ports and their environs.

This report presents a summary of the objectives and requirements of the NPW radiation monitoring program, describes the implementation of the program for the visits during 1994 and records the results of radiation measurements taken in the ports visited.

No releases of radioactive material were detected, nor were any radiation levels recorded in excess of normal background levels of ionising radiation, either during or subsequent to these visits.

PART I—GENERAL

INTRODUCTION

1. Eleven visits were made by six Nuclear Powered Warships (NPW) of the United States Navy to Australian ports in 1994. The Commonwealth Government requires that a radiation monitoring program be carried out in association with such visits to detect any release of radioactivity to the ports or their environs or any increase in external radiation levels above those due to natural background radiation.
2. This report presents a summary of the objectives and requirements of the NPW radiation monitoring program, describes the implementation of the program for the visits during 1994 and records the results of radiation measurements taken.

THE RADIATION MONITORING PROGRAM

3. The requirements for the monitoring program are laid down in 'Environmental Radiation Monitoring During Visits of Nuclear Powered Warships to Australian Ports—Requirements, Arrangements and Procedures, Department of Defence, May 1988'. These requirements were previously published in the 'Report and Guidelines on Environmental Radiation Monitoring During Visits to Australian Ports by Nuclear Powered Warships, Department of Science and Environment, September 1979'.
4. The monitoring program has two main components:
 - a. environmental monitoring, designed to detect the release of any radioactive material (eg waste) to the environment; and
 - b. direct radiation monitoring, designed to provide warning of any malfunction of the reactor of an NPW while in port, which might lead to a release of radioactivity.

Environmental Monitoring

5. The environmental radiation monitoring program is intended to provide assurance that there has been no infringement of Australian public health standards because of the release of radioactive material from the waste control and retention systems of a visiting NPW.
6. The relevant Australian public health standards are those endorsed by the National Health and Medical Research Council in 1980 ('Recommended Radiation Protection Standards for Individuals Exposed to Ionising Radiation', AGPS, 1981). These standards relate to permissible ionising radiation doses received by individuals from both external radiation sources and from the intake of radionuclides in air, water and foodstuffs.
7. **Internal radiation.** Internal radiation exposure of individuals could follow consumption of seafoods should these become contaminated with radioactive waste material. Accordingly, a marine environmental monitoring program is implemented to take samples of the surface layer of the bottom sediment and selected seafoods or seaweed (where available) from the vicinity of approved berths and anchorages.
8. These samples are analysed for evidence of cobalt-60 and other artificial gamma ray emitting radionuclides known to characterise the radioactive waste likely to be held in an NPW.
9. **External radiation.** When an NPW is at an alongside berth, gamma radiation surveys are undertaken at the wharf in those areas in the vicinity of the vessel designated as free for access by the public or by port employees. Surveys are made initially on the vessel's arrival and periodically thereafter for the duration of the visit using portable dose rate meters capable of measuring ionising radiation dose rates down to 0.01 $\mu\text{Sv/h}$.

10. Thermoluminescent dosimeters. In order to record the accumulated ionising radiation doses that might be received in the port environs following an accidental release of airborne radioactivity, a number of thermoluminescent dosimeters (TLD) are placed at selected locations. The TLD remain in position during the period that an NPW is in port or, in the event of an accident, would remain in position until the termination of the accident. Control TLD are exposed at the Australian Radiation Laboratory (ARL) in Melbourne and also in the port being visited, but remote from the NPW to provide a comparison with the TLD exposed in the field. Field and control TLD are returned to the ARL for measurement.

Direct Radiation Monitoring

11. In order to provide early warning of an NPW reactor malfunction at an alongside berth, fixed radiation detectors are located in the vicinity of the vessel to provide continuous monitoring of gamma radiation levels. The detectors cover the range 0.01 $\mu\text{Sv/h}$ to 100 $\mu\text{Sv/h}$ with an audible alarm set to trigger at a level of 1 $\mu\text{Sv/h}$. A significant release of radioactivity into the interior of the vessel from the reactor would be detected and initiate an alarm.

PROGRAM IMPLEMENTATION

The Monitoring Program

12. Groups which consist of members from the Australian Nuclear Science and Technology Organisation (ANSTO), the Health and Environmental authorities of the host State or Territory and the Royal Australian Navy (RAN) undertake the external radiation monitoring program. The composition of the groups varies in different ports; however, the Leader of the Radiation Monitoring Group is always a radiation protection officer from ANSTO.

13. The marine environmental monitoring program is a joint undertaking by the Australian Radiation Laboratory (ARL) of the Commonwealth Department of Human Services and Health and either the State concerned or, where the berth is in a naval establishment, the RAN. The collection of samples of sediment and seafood or seaweed is carried out by State authorities or by the RAN, nominally at quarterly¹ intervals at approved berths and anchorages. Samples are also taken prior to and immediately after each visit. The analysis and measurement of samples is undertaken by ARL. Details of the measurement method and detection capability are presented in Part III.

14. The routine sampling program may be discontinued at NPW berths and anchorages which are visited infrequently or where an adequate database has been established. When an NPW subsequently visits such a berth, samples are taken prior to and immediately after the visit and a further set of samples taken three months later.

Contingency Arrangements

15. Port safety organisations have been established at all ports approved for NPW visits and arrangements made so that in the event of a reactor accident they would be activated immediately. Simultaneously, radiation surveys would be initiated by Commonwealth officers in order to identify any radiation hazards. Prior to each visit, the Port Safety Organisation is brought to a state of readiness and briefings are conducted to familiarise key participants with the operational procedures and the tasks required of them in the event of an accident. Normally, an exercise is conducted prior to an NPW visit involving key members of the Port Safety Organisation.

¹ In practice, quarterly generally means 14 days either side of the end of the quarter. Should pre- or post-visit samples fall within two weeks of the due date for routine sampling, then the same set of samples will suffice for the routine and either pre- or post-visit samples. Authorities occasionally have difficulty in obtaining samples within these time scales.

PART II—NUCLEAR POWERED WARSHIP VISITS IN 1994

DARWIN NORTHERN TERRITORY

VISIT BY USS HELENA

16. USS HELENA, a nuclear powered Los Angeles class attack submarine of the US Navy, visited Darwin during the period 1–7 March 1994, berthing at the approved designated position, No. 5 Naval Buoy off Stokes Hill Wharf.

Radiation Monitoring

17. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment located on the bridge of AM(T) TAMMAR which was manned continuously and anchored in the vicinity.

Results

18. The gamma radiation dose rates measured by both fixed and portable monitoring equipment during the visit averaged 0.05 $\mu\text{Sv/h}$, indicating no significant variation above the natural background level.

19. TLD were exposed at eight designated locations during the visit. Control TLD were held in Darwin and at ARL. The range of dose measurements from the TLD for the visit showed no obvious increase above the normal range of background levels.

FREMANTLE (GAGE ROADS)

VISIT BY USS CARL VINSON

20. USS CARL VINSON, a nuclear powered Nimitz class aircraft carrier of the US Navy, visited Fremantle during the period 5–10 July 1994, anchoring at the approved designated anchorage in Gage Roads.

Radiation Monitoring

21. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment located on the bridge of TRV TAILOR which was manned continuously and anchored in the vicinity.

Results

22. The gamma radiation dose rates measured by both fixed and portable monitoring equipment during the visit averaged 0.05 $\mu\text{Sv/h}$ indicating that there was no observable increase in the external gamma radiation level above background.

23. TLD were exposed at five designated locations during the visit. Control TLD were held in Perth and at ARL. The range of dose measurements from the TLD for the visit showed no obvious increase above the normal range of background levels.

HMAS STIRLING, GARDEN ISLAND, WESTERN AUSTRALIA

VISIT BY USS ARKANSAS

24. USS ARKANSAS, a nuclear powered Virginia class cruiser of the US Navy, visited HMAS STIRLING during the period 5–10 July 1994, berthing at the Submarine Wharf.

Radiation Monitoring

25. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment located in the Guardhouse which was manned continuously. In addition, measurements of gamma radiation levels were taken daily using hand-held dose rate meters in those areas around the vessel which were accessible to personnel on the base.

Results

26. The gamma radiation dose rates measured by both fixed and portable monitoring equipment during the visit averaged 0.14 $\mu\text{Sv/h}$ indicating that there was no observable increase in the external gamma radiation level above background.

27. TLD were exposed at six designated locations during the visit. Control TLD were held in Perth and at ARL. The range of dose measurements from the TLD for the visit showed no obvious increase above the normal range of background levels.

VISIT BY USS ASHEVILLE

28. USS ASHEVILLE, a nuclear powered Los Angeles class attack submarine of the US Navy, visited HMAS STIRLING during the period 5–15 July 1994, berthing at the Submarine Wharf.

Radiation Monitoring

29. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment located in the Guardhouse which was manned continuously. In addition, measurements of gamma radiation levels were taken daily using hand-held dose rate meters in those areas around the vessel which were accessible to personnel on the base.

Results

30. The gamma radiation dose rates measured by both fixed and portable monitoring equipment during the visit averaged 0.14 $\mu\text{Sv/h}$ indicating that there was no observable increase in the external gamma radiation level above background.

31. TLD were exposed at six designated locations during the visit. Control TLD were held in Perth and at ARL. The range of dose measurements from the TLD for the visit showed no obvious increase above the normal range of background levels.

VISIT BY USS INDIANAPOLIS

32. USS INDIANAPOLIS, a nuclear powered Los Angeles class attack submarine of the US Navy, visited HMAS STIRLING during the periods 20–24 October 1994, 4–6 November 1994 and 13–11 November 1994, berthing at the Submarine Wharf.

Radiation Monitoring

33. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment located in the Guardhouse which was manned continuously. In addition, measurements of gamma radiation levels were taken daily using hand-held dose rate meters in those areas around the vessel which were accessible to personnel on the base.

Results

34. The gamma radiation dose rates measured by both fixed and portable monitoring equipment during the visits averaged $0.12 \mu\text{Sv/h}^{-1}$ and $0.20 \mu\text{Sv/h}^{-1}$ respectively indicating that there was no observable increase in the external gamma radiation level above background.

35. TLD were exposed at six designated locations during the visit. Control TLD were held in Perth and at ARL. The range of dose measurements from the TLD for the visit showed no obvious increase above the normal range of background levels.

MELBOURNE VICTORIA

VISIT BY USS ARKANSAS

36. USS ARKANSAS, a nuclear powered Virginia class cruiser of the US Navy, visited Melbourne during the period 16–22 July 1994, berthing at the approved berth on Breakwater Pier at Williamstown.

Radiation Monitoring

37. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment which was located in the Port of Melbourne Authority building, on Breakwater Pier, which was manned continuously.

Results

38. The gamma radiation dose rates measured by both fixed and portable monitoring equipment during the visit averaged $0.10 \mu\text{Sv/h}$, indicating no significant variation above the natural background level.

39. TLD were exposed at seven designated locations during the visit. Control TLD were held in Melbourne and at ARL. The range of dose measurements from the TLD for the visit showed no obvious increase above the normal range of background levels.

HOBART TASMANIA

VISIT BY USS CARL VINSON

40. USS CARL VINSON, a nuclear powered Nimitz class aircraft carrier of the US Navy, visited Hobart during the period 17–22 July 1994, anchoring at the approved designated anchorage in the Derwent River.

Radiation Monitoring

41. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment located on the bridge of AM(T) WALLAROO which was manned continuously and anchored in the vicinity.

Results

42. The gamma radiation dose rates measured by both fixed and portable monitoring equipment during the visit averaged 0.10 $\mu\text{Sv/h}$, indicating no significant variation above the natural background level.

43. TLD were exposed at six designated locations during the visit. Control TLD were held in Hobart and at ARL. The range of dose measurements from the TLD for the visit showed no obvious increase above the normal range of background levels.

VISIT BY USS INDIANAPOLIS

44. USS INDIANAPOLIS, a nuclear powered Los Angeles class attack submarine of the US Navy, visited Hobart during the period 20–23 November 1994, anchoring at the approved designated anchorage in the Derwent River.

Radiation Monitoring

45. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment which was located on the bridge of the Tug MYALLA which was manned continuously and anchored in the vicinity.

Results

46. The gamma radiation dose rates measured by both fixed and portable monitoring equipment during the visit averaged 0.10 $\mu\text{Sv/h}$, indicating no significant variation above the natural background level.

47. TLD were exposed at six designated locations during the visit. Control TLD were held in Hobart and at ARL. The range of dose measurements from the TLD for the visit showed no obvious increase above the normal range of background levels.

BRISBANE QUEENSLAND

VISIT BY USS OMAHA

48. USS OMAHA, a nuclear powered Los Angeles class attack submarine of the US Navy, visited Brisbane during the period 17–22 July 1994, berthing at No. 1 Wharf, Fisherman Islands.

Radiation Monitoring

49. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment located in a State Emergency Services caravan, located on the Grain Wharf, which was manned continuously. In addition, measurements of gamma radiation levels were taken using hand-held dose rate meters in the areas around the vessel which were accessible to personnel on the wharf.

Results

50. The average gamma radiation dose rates measured by both fixed and portable monitoring equipment during the visit was in the range 0.20 $\mu\text{Sv/h}$, indicating no significant variations above the natural background level.

51. TLD were exposed at eight designated locations during the visit. Control TLD were held in Brisbane and at ARL. The range of dose measurements from the TLD for the visit showed no obvious increase above the normal range of background levels.

PART III—MARINE ENVIRONMENTAL SAMPLING

Measurement Method

52. Each sample is measured for at least 10 000 seconds, in a standard geometry, in a low background gamma ray spectrometer with a hyperpure germanium detector. Each gamma ray spectrum is scrutinised over the energy range of 50 to 1500 KeV for evidence of cobalt-60 and other artificial gamma ray emitting radionuclides.

Detection Capability

53. The measurement method used has sufficient sensitivity to detect concentrations of gamma ray emitting radionuclides in shellfish which, based upon typical intakes of shellfish, would result in no more than one per cent of the annual limits for members of the public as given in the '1990 Recommendations of the International Commission on Radiological Protection (ICRP Publication 60)' which are currently in the process of being adopted for Australia by the National Health and Medical Research Council.

54. For surface layer of bottom sediment, the measurement method used has sufficient sensitivity to detect artificial gamma ray emitting radionuclides at concentrations at least as low as 40 millibecquerels per gram of sediment.

Marine Environmental Monitoring

55. Marine environmental samples appropriate to each berth visited in Hobart, Melbourne, Darwin, HMAS STIRLING, Gage Roads (Fremantle) and Brisbane were collected according to the agreed sampling program.

56. All samples were analysed at ARL. Certificates of analysis issued by ARL showed that no radionuclide was detected that would be characteristic of the radioactive waste associated with NPW operations.

PART IV—CONCLUSIONS

57. The program of radiation monitoring and marine environmental sampling implemented for visiting NPW during 1994 was consistent with the Commonwealth Government's requirements.

58. There was no indication of any infringement of Australian public health standards. Radiation monitoring did not detect any release of radioactive materials, nor did radiation measurements indicate any value in excess of background levels of ionising radiation either during or subsequent to these visits.